

(19) World Intellectual Property
Organization
International Bureau



PCT

534, 867
Rec'd PCT/PTO 12 MAY 2005



10/534867

(10) International Publication Number
WO 2004/043897 A1

(43) International Publication Date
27 May 2004 (27.05.2004)

- (51) International Patent Classification⁷: C07C 201/02, 203/04
- (21) International Application Number:
PCT/EP2003/012375
- (22) International Filing Date:
6 November 2003 (06.11.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
MI2002A002409
14 November 2002 (14.11.2002) IT
- (71) Applicant (for all designated States except US): DINA-MITE DIPHARMA S.p.A. IN ABBREVIATED FORM [IT/IT]; Dipharma S.p.A., Via XXV Maggio, 40, I-33036 Mereto di Tomba (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): SCUBLA, Tiziano [IT/IT]; Via Bonanni, 32, I-33037 Pasian di Prato (IT). FRANCESCUTTI, Nevio [IT/IT]; Via Caravaggio, 21, I-33070 San Giovanni di Casarsa (IT). GORASSINI, Fausto [IT/IT]; Via Codroipo, 30, I-33100 Udine (IT). CASTALDI, Graziano [IT/IT]; Via Livia Gallina, 5, I-28072 Briona (IT).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
- with international search report
 - before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A PROCESS FOR THE PURIFICATION OF 1,4-BUTANEDIOL MONONITRATE

(57) Abstract: A process for the purification of 1,4-butanediol mononitrate from 1,4-butanediol dinitrate and 1,4-butanediol, by selective extraction with solvents is herein disclosed.

WO 2004/043897 A1

A PROCESS FOR THE PURIFICATION OF 1,4-BUTANEDIOL MONONITRATE

FIELD OF THE INVENTION

The present invention relates to a process for the purification of 1,4-butanediol mononitrate (BDMN) from 1,4-butanediol dinitrate (BDDN) and 1,4-butanediol (BD) in an efficient, easily controllable way, which is therefore
5 safer for operators.

TECHNOLOGICAL BACKGROUND

BDMN is a key intermediate in the synthesis of nitric oxide (NO)-releasing NSAIDs, i.e. non-steroidal anti-inflammatory drugs which release nitric oxide. NO-NSAIDs have antipyretic and anti-inflammatory activities,
10 but lower gastrointestinal toxicity than other non-steroidal anti-inflammatory medicaments. Examples of NO-NSAIDs are NO-acetylsalicylic acid, NO-diclofenac, NO-naproxen, NO-ketoprofen and NO-ibuprofen. The preparation of NO-naproxen is described, for example, in WO 01/10814.

The industrial production of BDMN by reduction or hydrolysis from
15 BDDN, is problematic and poorly selective, as the synthesis of BDDN involves problems concerning production, storage and transport similar to those connected with the use of nitroglycerin.

Mono-nitration of BD with the methods available to date is also problematic and poorly selective on an industrial scale, as dangerous
20 decomposition reactions easily occur when a strong oxidizer (nitric acid) is contacted with an unstable substrate.

Moreover, BDMN obtained by mono-nitration of BD has to be separated from unreacted BDDN and BD. Such separation is, however, potentially dangerous, in that BDMN has, like BDDN, explosive
25 characteristics, therefore neither crystallization nor distillation techniques can

be employed. In fact, both BDMN and BDDN are liquid at room temperature and they can decompose upon crystallization due to friction or impaction. Analogously, distillation involves evident hazards owing to the recovery of the explosive compound in the pure form. In view of their chemical-physical characteristics, distillation of a mixture containing BDDN and BDMN would require heating to a temperature at which spontaneous, explosive decomposition could take place.

There is therefore need for a process for the purification of BDMN from BD and BDDN which avoids crystallization or distillation.

10 **DETAILED DISCLOSURE OF THE INVENTION**

It has now been found that BDMN can be selectively separated from BD and BDDN in industrially advantageous yields by subsequent extractions with water and a water-immiscible organic solvent.

Object of the present invention is therefore a process for the separation of 1,4-butanediol mononitrate from a solution of 1,4-butanediol dinitrate and 1,4-butanediol in a water-immiscible organic solvent, which process comprises the following steps:

- a) extraction of BDMN from said solution by water;
- b) extraction of BDMN from the resulting aqueous solution, by an organic solvent immiscible with water.

According to a preferred aspect, the invention comprises a further step c), which consists in washing the aqueous solution exiting from the extraction column "(A)" with the same organic solvent used in the subsequent step b). Said washing allows to remove BDDN from the aqueous phase before subjecting it to step b).

According to a further preferred aspect, the invention comprises a further step d) in which the residual organic solution from step a) is extracted with the aqueous phase exiting from column (B). The resulting BDMN-

enriched aqueous solution is recycled to the first extraction column (A).

Typical water-immiscible organic solvents which can be used according to the invention are chlorinated solvents, for example C1-C4 alkyl mono-, di-, tri- or tetrachlorides, preferably dichloromethane, trichloromethane, 5 tetrachloromethane, trichloroethane and tetrachloroethane, in particular dichloromethane. Preferably, the water-immiscible organic solvent in the solution of BD, BDMN and BDDN to be subjected to the separation process and the water-immiscible organic solvent used in the extraction according to step b) are the same.

10 The process according to the invention consists of one or more extraction cycles with water and a water-immiscible organic solvent according to steps a) and b) and optionally of steps c) and/or d). Preferably, the process comprises 1 to 4 a) and b) cycles, preferably 2 or 3, most preferably 2.

If desired, the organic solution containing purified BDMN obtained 15 with the process of the invention can be concentrated.

A further object of the invention is highly pure 1,4-butanediol mononitrate, typically higher than 99% pure, as obtainable by the process of the invention.

A further object of the invention is a solution of 1,4-butanediol 20 mononitrate in a water-immiscible organic solvent, substantially free from 1,4-butanediol dinitrate, as obtainable by the process of the invention.

Solutions of 1,4-butanediol mononitrate substantially free from 1,4-butanediol dinitrate in an organic solvent selected from dichloromethane, trichloromethane, tetrachloromethane, trichloroethane and tetrachloroethane, in 25 particular dichloromethane, are preferred.

The solution containing BDMN, BDDN and BD to be subjected to the extraction process according to the invention can be obtained either with conventional synthetic methods in a water-immiscible solvent or with a novel

process for the mononitration of 1,4-butanediol, which is a further object of the invention.

Said method consists in the nitration of 1,4-butanediol by treatment with "stabilized" nitric acid in a water-immiscible organic solvent selected
5 from those defined above.

The expression "stabilized" nitric acid means a nitric acid solution diluted with water, having concentration ranging from about 83 to about 85%, preferably from about 84.5 to about 84.8%, and substantially free from nitrous acid and nitrogen oxides. The expression "substantially free from nitrous acid
10 and nitrogen oxides" means that their concentration is typically lower than 10 ppm, preferably lower than 5 ppm. Said "stabilized" nitric acid is also an object of the present invention.

The preparation of "stabilized" nitric acid can be carried out, for example, by dilution of fuming nitric acid with water to a concentration
15 ranging from about 83 to about 85% followed by treatment with an amount of an agent able to remove nitrous acid and nitrogen oxides present therein. Said agent can be, for example, urea or sulfamic acid, preferably urea, in amounts ranging from about 0.3 to about 1% w/w. The same result can be obtained by addition of an aqueous solution of said agent to fuming nitric acid. The
20 contact time of said agent with nitric acid required to completely remove the nitrous acid and nitrogen oxides ranges from about 80 minutes to about 130 minutes. When said agent is urea, the amount ranges from about 0.6 to about 1% w/w, preferably from about 0.7 to about 1% w/w and the contact time preferably ranges from about 95 to about 120 minutes.

25 The "stabilized" nitric acid according to the invention should be used within approx. three hours from stabilization, as in time nitrous acid and nitrogen oxides are released again in such concentrations as to trigger strong decomposition reactions.

The weight ratio of "stabilized" nitric acid to 1,4-butanediol preferably ranges from about 11 : 1 to about 14.5 : 1 and the nitration is preferably carried out for a time ranging between about 10 and about 30 minutes.

5 In this manner industrially advantageous yields in 1,4-butanediol mononitrate are obtained and hazards for operators are lower than those associated with nitration with concentrated nitric acid, sometimes added with sulfuric acid or urea to remove nitrous acid.

Before being subjected to the extraction process of the invention, the nitrated solution can be treated to remove by-products and unreacted starting
10 products, then suitably concentrated. Said solution is, in fact, a crude mixture of BDMN, by-product BDDN, unreacted BD and nitric acid in the organic solvent, also containing other by-products deriving from dehydration and/or oxidation. The solution is first partially neutralized with a sodium hydroxide concentrated solution, thus extracting most of the unreacted BD in the
15 resulting sodium nitrate aqueous solution. The organic phase is then concentrated by evaporation and neutralized with a diluted basic solution.

The solution subjected to the separation process of the invention preferably contains BDMN in amounts ranging from about 11% to about 15% w/w, preferably 11% w/w; BDDN in amounts ranging from about 3 to about
20 4.5% w/w, preferably 4%; BD in amounts ranging from about 0.2 to about 0.8% w/w (with respect to BDMN). The extraction is more efficient with more concentrated solutions, but when total nitroesters concentrations are above 15% w/w, the solutions have explosive character.

The extraction according to steps a) and b) is preferably carried out
25 using two or more liquid-liquid counter-current extraction columns, preferably two, three or four, more preferably two, herein referred to as column (A), for step a) and column (B), for step b). Columns (A) and (B) are preferably plate columns having 45 - 55 plates and optionally a decanter at the top and one at

the bottom. Particularly suitable are liquid-liquid counter-current extraction columns for nominal flow rates of about 5-50 l/h, with a decanter at the top and one at the bottom. According to a particularly preferred extraction method, said extractions are carried out with columns mod. E60/50G from
5 Kühni (Basilea -Switzerland).

The two extractions are carried out at temperatures compatible with the thermal stability of BDMN and BDDN, namely at a temperature below the boiling point of the organic solvent, preferably at room temperature.

Figure 1 shows the essential elements of a purification plant according
10 to the invention, namely extraction column (A), extraction column (B) and a reactor (C) for the optional step c), wherein the process is carried out using dichloromethane as the solvent. When dichloromethane is replaced with an organic solvent lighter than water, fluids will be fed to the extraction columns (A) and (B) in an opposite manner.

15 For extraction step a), the dichloromethane solution of BDMN, BDDN and BD, i.e. the "crude" obtainable from the treatment described above, is fed to the top of a first extraction column (A), while water is fed to the bottom of said column. All the residual BD, most of the BDMN and a very small aliquot of BDDN in aqueous solution exit the top decanter of column (A). The
20 raffinate consisting of a dichloromethane solution containing most of the BDDN and a small amount of BDMN exits the bottom of the column.

For extraction step b), the aqueous solution of BDMN, residual BD and the very small amount of BDDN from the first extraction column (A) is fed to the base of a second extraction column (B), while fresh dichloromethane is fed
25 to the head. Water with all the residual BD and some BDMN exit the head of the second column, while the extract, i.e. a dichloromethane solution containing purified BDMN and the negligible amount of BDDN, exit the bottom.

Optional step c), which is carried out in an extractor (C), allows to increase the purity level of BDMN and can be effected as follows. The aqueous solution exiting the first extraction column (A) is treated with a suitable amount of dichloromethane ranging from about 7 to about 20% w/w with respect to the chloromethylene solution fed to the column (A). Treatment allows to remove BDDN which, although sparingly water-soluble (solubility <0.05%), is still present at rather high concentrations compared with BDMN (approx. 1-2%). Extractor (C) can be, for example, a conventional reactor, with a decanter downstream. After decantation, the aqueous phase now substantially containing only BDMN and the residual BD is fed to the second extraction column (B). The organic phase containing BDDN is recycled.

For step d), the aqueous phase from the second extraction column (B), containing a very small amount of BDMN, is mixed with the dichloromethane raffinate from column (A), which in turn contains a small amount of BDMN. Extraction and subsequent decantation provide an aqueous phase enriched in BDMN, which is recycled to the first extraction column (A). In this manner, yield in BDMN can be further increased.

From the scheme reported in Figure 1 it is evident that the process of the invention also provides a remarkable savings of extraction water. In fact, water that contains the residual BD exiting the top of the second extraction column (B) is recycled to the first extraction column (A) until its content in BD is compatible with the extraction process.

From the above description it will be appreciated that the process of the invention allows to separate BDMN from BD and BDDN with low hazards, good selectivity and high yields. The extraction yield (expressed as percentage ratio of purified BDMN to BDMN present in the crude solution) is above 90% w/w.

Furthermore, the resulting organic solution contains highly pure

BDMN, typically above 99.0% pure. For example, the dichloromethane solution contains BDMN with purity from about 99.5 to about 99.9%, in amounts ranging from about 5 to about 8% w/w. The solution is therefore substantially free from BDDN. The residual amount of BDDN in the organic solvent is, in fact, below 0.2% and in case of dichloromethane is below 0.15%.

If desired, once the extraction is completed, the purified BDMN organic solution can be finally concentrated, for example under reduced pressure, to a concentration of about 15% w/w in order to make transport or storage easier. The use of solutions with higher BDMN contents can be potentially dangerous to operators.

The present invention is further illustrated by the following examples.

EXAMPLES

Example 1 - Purification with water/dichloromethane

Two extraction columns Kühni mod. E60/50G are used. The crude solution (containing about 11% BDMN and about 4% BDDN) is fed (6.5 kg/h) to the top of the first column, wherein it encounters the extracted water (42.3 kg/h) (containing about 0.3% of BDMN) that exit the top of the second column and flows backwards. The raffinate (containing about 0.6% BDMN and about 6% BDDN) exits the bottom of the first column and extraction water (42.9 kg/h), rich in BDMN (about 1.6% BDMN and <0.05% BDDN) exits the top and is passed through de-emulsifier, then fed to the bottom of the second column, wherein it encounters fresh dichloromethane flowing backwards (11.1/h). Water with some BDMN exits the top of second column and is recycled to the first column, while the dichloromethane solution containing purified BDMN (about 6% w/w BDMN) exits the bottom. BDMN, which has 99.5% purity (0.5% of BDDN) in the extract, is then concentrated to 15% w/w. The extraction yield, expressed as the ratio of purified BDMN to BDMN present in the crude solution, is about 94% w/w.

Example 2 - Purification with water/dichloromethane.

The plant is substantially the same as that of example 1, in which a 5 liters reactor equipped with a stirring system and a separator is fitted between the two distillation columns. In this step, BDDN solubilised in the water exiting the top of the first column is extracted with dichloromethane (1.0 kg/h) and recycled after separation. The final extract is thus sufficiently pure (BDDN <0.1%).

Example 3 - Preparation of "stabilized" nitric acid.

A stainless steel reactor, equipped with condenser and stirrer, is loaded with 90 kg of diluted nitric acid (84.7%), with nitrous acid content of approx. 0.09%. The nitric acid solution is added with 675 g of urea beads, under stirring. The solution is kept under stirring for about 90 minutes, then disappearance of all the nitrous acid and nitrogen oxides is checked, both by observation of the color of the solution and determination with permanganate. If necessary, further urea is added in small portions, until complete removal of the nitrous acid and nitrogen oxides.

Example 4 - 1,4-Butanediol-mononitrate.

A stainless steel reactor is loaded in succession with 931 g of dichloromethane and 385 g of "stabilized" nitric acid. The dispersion is cooled to about 0°C under stirring, then 50 g of a 70/30 solution of 1,4-butanediol in dichloromethane is added in a single portion. The reaction mixture is kept under stirring at temperatures ranging from about -2°C to 2°C. Nitration kinetics is monitored on samples of the reaction mixture. After 20 minutes the reaction is quickly quenched by pouring it into an ice/water (385 g) mixture, then neutralized with 433 g of 40% NaOH, keeping the temperature below 15°C. The organic phase containing 1,4-butanediol-mononitrate (19.2 g), 1,4-butanediol-dinitrate (6.4 g) and 1,4-butanediol (0.1 g) is then separated and subjected to the subsequent purification.

CLAIMS


1. A process for the separation of 1,4-butanediol mononitrate from a solution of 1,4-butanediol dinitrate and 1,4-butanediol in a water-immiscible organic solvent, comprising:
 - a) extraction of 1,4-butanediol mononitrate from said solution by water;
 - b) extraction of 1,4-butanediol mononitrate from the resulting aqueous solution, by a water-immiscible organic solvent.
2. A process as claimed in claim 1, characterized in that the extraction according to steps a) and b) is carried out in counter-current in two or more extraction columns.
3. A process as claimed in claim 1, wherein the extraction according to steps a) and b) is carried out in counter-current in 2, 3 or 4 extraction columns.
4. A process as claimed in claim 3, wherein the extraction according to steps a) and b) is carried out in counter-current in 2 extraction columns.
5. A process according to any one of claims 1 - 4 further comprising washing the aqueous phase from step a) with the same water-immiscible organic solvent as that used in the subsequent step b).
6. A process according to any one of claims 1 - 4, comprising the extraction of the resulting organic solution from step a) with the aqueous phase from step b) and the recycle of the aqueous solution to the extraction column of step a).
7. A process according to any one of claims 1 - 6, comprising 1 to 4 extraction cycles according to steps a) and b).
8. A process according to any one of claims 1 - 7, wherein the water-immiscible organic solvent is an organic chlorinated solvent.
9. A process as claimed in claim 8, wherein the chlorinated solvent is

selected from the group consisting of dichloromethane, trichloromethane, tetrachloromethane, trichloroethane and tetrachloroethane.

10. A process as claimed in claim 9, wherein the chlorinated solvent is dichloromethane.

5 11. 1,4-Butanediol mononitrate with purity above 99%.

FIGURE 1



INTERNATIONAL SEARCH REPORT

International Application No.

PCT/EP 03/12375

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 C07C201/02 C07C203/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 C07C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, INSPEC, COMPENDEX, BEILSTEIN Data, CHEM ABS Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 01/10814 A (NICOX SA ; CASTALDI GRAZIANO (IT); OLDANI ERMINIO (IT); BENEDINI FRANC) 15 February 2001 (2001-02-15) cited in the application	1,8,9,11
Y	page 2, line 15 - line 18 4-nitroxybutan-1-ol used as starting material in the examples prepared according to W098/25918 page 4, line 22 - line 24	2-7,10
X	WO 98/25918 A (DROUX SERGE ; JOLY PASCAL (FR); PETIT FRANCIS (FR); GIGLIOTTI GIUSEPPE) 18 June 1998 (1998-06-18)	1,8,9,11
Y	preparation 1; preparation 3, stade B; preparation 4, stade B page 5, line 16 - line 19 claim 10	2-7,10
----- -/-		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

27 February 2004

Date of mailing of the international search report

16/03/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 apo nl,
Fax: (+31-70) 340-3016

Authorized officer

Seelmann, M

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/EP 03/12375

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	K.TREVES ET AL.: "Henry's law constants of some beta-, gamma- and delta-hydroxy alkyl nitrates of atmospheric interest" ENVIRON.SCI.TECHNOL., vol. 34, 2000, pages 1197-1203, XP002271697 experimental section; method 1 page 1200, left-hand column, paragraph 1; table 1	2-7,10
Y	----- KIRK-OTHMER: "Extraction (liquid-liquid)" ENCYCLOPEDIA OF CHEMICAL TECHNOLOGY, vol. 10, 1993, pages 136-139, XP002271719 the whole document -----	2-7,10

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 03/12375

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0110814	A	15-02-2001	IT MI991753 A1	05-02-2001
			AT 251109 T	15-10-2003
			AU 6438500 A	05-03-2001
			BR 0012915 A	04-06-2002
			CA 2380116 A1	15-02-2001
			CN 1367773 T	04-09-2002
			DE 60005682 D1	06-11-2003
			DK 1200386 T3	22-12-2003
			WO 0110814 A1	15-02-2001
			EP 1200386 A1	02-05-2002
			EP 1384707 A1	28-01-2004
			HU 0202435 A2	28-11-2002
			JP 2003506425 T	18-02-2003
			NO 20020515 A	01-02-2002
			PL 353092 A1	06-10-2003
			TR 200200290 T2	21-05-2002
WO 9825918	A	18-06-1998	FR 2757159 A1	19-06-1998
			WO 9825918 A1	18-06-1998